



TIPO	D mm	D1	B	B1	A	L	L1	H	H1	C	C1
BG125	125	150	55	85	325	150	97	250	7.5	30	50
BG160	160	190	60	90	325	150	97	250	15	50	60
BG200	200	230	60	90	400	200	106	300	15	65	80
BG250	250	290	70	110	400	200	118	300	15	65	80
BG315	315	360	80	120	450	200	142	400	15	80	100
BG315*	315*	360	90	130	450	200	142	400	15	80	100
BG400	400	450	90	140	500	250	142	450	20	100	125
BG400*	400*	450	80	130	500	250	142	450	20	100	125
BG400**	400**	450	100	150	500	250	142	450	20	100	125

TIPO	D2	d	b	t	s	h	l	8xØ	8xM	R max. Kg.	ROD.
BG125	45	30	8	33	20	300	300	25	24	3640	6011
BG160	60	30	8	33	24	300	300	25	24	5510	6211
BG200	60	35	10	38	24	350	350	25	24	8520	6311
BG250	60	40	12	43	24	350	350	25	24	10800	22211
BG315	65	50	12	53.5	25	450	350	27	26	13680	22212
BG315*	65	50	14	53.5	25	450	350	27	26	13680	22212
BG400	95	50	14	53.5	30	500	400	31	30	19800	22218
BG400*	95	50	14	53.5	30	500	400	31	30	19800	22218
BG400**	95	50	14	53.5	30	500	400	31	30	19800	22218